

5/20/21

AQUAPURE™ FP C8 GR
2601216

Industrial applications

563 South Leonard Street
Waterbury, CT 06708
: 203-756-5521
203-756-9017

Emergency Phone Number
1 (800) 424-9300
1 (703) 527-3887

No signal word

Not a hazardous substance or mixture

Not a hazardous substance or mixture. Material intended for Industrial use. Refer to SDS for safe use and handling. Always keep this product away from children. This product may be harmful if ingested. Industrial experience has shown no significant inhalation hazard or skin irritation when good industrial hygiene practices are followed. Keep this product from contamination by making sure that no other products are introduced once drum is open.

IN CASE OF FIRE: ALCOHOL FOAM, CO2, DRY CHEMICAL EXTINGUISHER SHOULD BE USED. FIREFIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS.

Keep from freezing

Distillates, (petroleum), hydrotreated light		64742-47-8	20-30%
poly(oxy-1,2,ethanediyl),a-tridecyl-w-hydroxy-,branched)	-	69011-36-5	<5%

If on skin(on hair): Wash off immediately with soap and plenty of water while removing all contaminated clothing and shoes. In case of persistent skin irritation, consult a physician.

If in eyes: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritated, call doctor.

If swallowed: Rinse mouth. Do NOT induce vomiting. Call a physician or poison control center immediately.

Irritation of eyes and skin.

This product can cause mild, transient skin irritation. The severity of irritation will depend on the amount of material that is applied to the skin and the speed and thoroughness that it is removed. Symptoms include redness, itching, and burning of the skin. Repeated or prolonged skin contact can produce moderate irritation(dermatitis).

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Keep victim under observation.

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Carbon oxides may be produced. Warning! Spills produce extremely slippery surfaces.

Wear chemical resistant protective equipment and self contained breathing apparatus (SCBA).

Stop spill at source.

Caution: Spilled material may be slippery.

If trained in accordance 29 CFR 1910.120, leaks should be stopped. Spills should be contained and cleaned immediately. Persons performing clean up work should wear adequate personal protective equipment and clothing. Spills and releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

Absorb the chemical onto sand, vermiculite, or any other non-combustible absorbent, and collect into containers for later disposal.

Wash hands thoroughly after handling.

Wear rubber gloves, goggles and chemical protective clothing.

Eating, drinking and smoking in the work area is prohibited.

Keep away from heat and sources of ignition. Freezing will affect the physical condition and may damage the material. Incompatible with oxidizing agents.

No hazardous ingredients	Not established		

PVC or other plastic material gloves.

Wear chemical safety goggles.

Not listed by IARC, NTP, OSHA, ACGIH
Eyes, Skin, Inhalation, Ingestion

Distillates,petroleum hydrotrated light->1000 mg/L 96 h
Distillates, Petroleum hydrotreated light-EC50->1000 mg/L 48 h
Will biodegrade readily

No data available
Unlikely
Disperses in water.
No data available

Dispose of in accordance with local, state and federal regulations.

NOT D.O.T REGULATED

The chemicals in this product are not subject to SARA Title III , Section 313 Reporting Requirements.

No Proposition 65 listed components in this formula

All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.