



et t eet

Better Chemistry. Better Business.

3.30.21

Item 2204002

Electrocoat

Electrocoat

Electrocoat Metal Surface Protectant

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention .

Absorb spillage to prevent material damage.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

t e Store in corrosive resistant high density polyethylene container.

e t t Inhalation vapor = 81.2% Inhalation dust = 78.5%

te t

e e	e	t e e e t e	e t t
Dipropylene Glycol Monomethyl Ether	-	34590-94-8	<5%
Hexafluorozirconic acid	-	12021-95-3	<1%

te t

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

te t t

If on skin(on hair): Take off immediately all contaminated clothing. Rinse with water/safety shower. Call doctor if irritation persists.

te e t t

If in eyes: Rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If irritated, call doctor.

te e t

If swallowed: Rinse mouth. Do NOT induce vomiting.

t t t t e t

e

Irritation of eyes and skin.

This product can cause mild, transient skin irritation. The severity of irritation will depend on the amount of material that is applied to the skin and the speed and thoroughness that it is removed. Symptoms include redness, itching, and burning of the skin. Repeated or prolonged skin contact can produce moderate irritation(dermatitis).

t e te e tte t

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Keep victim under observation.

t e t e
e t e

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

e
t e e

Carbon oxides may be produced.

e te t ee e t
e t e te

Wear chemical resistant protective equipment and self contained breathing apparatus (SCBA).

et
t e t e

Stop spill at source.

e t t	Hazardous Polymerization will not occur.
e t t	Stable under normal conditions
t	Hazardous polymerization does not occur.
e t	
t e te	Avoid contact with strong oxidizers and strong acids.

t t	Dipropylene Glycol Monmethyl Ether-LD50(Rat)->5000 mg/kg
e t t	Dipropylene Glycol Monmethyl Ether-LD50-Rabbit-9510 mg/kg
t t	Severe irritation or burns to skin, eyes and respiratory system
e te e e t	Irritation/ burns of skin and eyes.
e	Not listed by IARC, NTP, OSHA, ACGIH
te e	Eyes, Skin, Inhalation, Ingestion

e te e	Not Available
e t	
B t e t	No data available
B t te t	Unlikely
te e t	Disperses in water.
e e t e t	No data available

Dispose of in accordance with local, state and federal regulations.

e	1760
e e	CORROSIVE LIQUID, N.O.S., (CONTAINS HEXAFLUOROZIRCONIC ACID),
t e	8
	II
	154