

3/19/21

AQUAEASE® SLA 2300
2052000

Industrial applications



Methanesulfonic Acid	-	75-75-2	~20%
Diethylene Glycol Butyl Ether	-	112-34-5	~10%

Remove exposed person to fresh air and support breathing as needed.

Immediately remove contaminated clothing under a safety shower. Flush all affected areas with large amounts of water for 15 minutes. DO NOT attempt to neutralize with chemical agents. Obtain medical advice.

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Do not induce vomiting. Immediately rinse mouth and drink plenty of water. If vomiting occurs, keep head low so that the stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person. Do not use mouth-to-mouth method if victim ingested the substance.

Symptoms may include irritation to the nose, throat and upper respiratory tract.

Adverse symptoms may include the following: Symptoms may include redness, pain, blurred vision, eye burns and permanent eye damage.

Adverse symptoms may include the following: May cause redness, pain and severe skin burns.

Adverse symptoms may include the following: Symptoms may include severe burns of the mouth, throat and stomach. Ingestion of large quantities may cause gastrointestinal irritation, vomiting and diarrhea.

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Fire fighters should enter area only if they are protected from all contact with the material. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

Wear chemical goggle, gloves and face shield and protective clothing.

Prevent spilled product from drains, sewers, waterways and soil.

Absorb the chemical onto sand, vermiculite, or any other non-combustible absorbent, and collect into containers for later disposal.

N/A

N/A

No specific test data related to reactivity available to this product or its ingredients.

Stable under normal conditions

Corrosive in presence of steel

Reacts violently with strong bases. Contact with metals may release flammable hydrogen gas.

Extreme humidity, excess heat.

Metals, strong oxidizing agents and strong bases. Do not mix with solutions containing bleach or ammonia.

Carbon Dioxide, Carbon Monoxide

Methanesulfonic acid-LD50(Rat)-649 mg/kg

Diethylene Glycol Butyl Ether-LD50(rat)-3305 mg/kg

Methanesulfonic acid LD50(Rabbit)->1000 mg/kg

Diethylene Glycol Butyl Ether, LD50 (rabbit)-2764 mg/kg

Irritation or burns to skin, eyes and respiratory system

Not listed by IARC, NTP, OSHA, ACGIH

Eyes, Skin, Inhalation, Ingestion

no data available

Not Available

Not known

Pronounced solubility and mobility

Not known

Dispose of in accordance with local, state and federal regulations.

3265

CORROSIVE LIQUID,ACIDIC,ORGANIC, NOS(ALKANE SULFONIC ACID)

8

II

153

Diethylene Glycol Butyl Ether-

All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.