



Safety Data Sheet

Better Chemistry. Better Business

DRY SLICK

9/18/18

Product Name: DRY SLICK

Product Code :2810018

Recommended use of the chemical and restrictions on use:Industrial applications

563 South Leonard Street

Waterbury, CT 06708

: 203-756-5521

203-756-9017

Emergency Phone Number

1 (800) 424-9300

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call poison center/doctor if you feel unwell.

If in eyes: Wash cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

In case of fire: Use water spray (fog), foam, dry chemicals, carbon dioxide, or other type of vapor producing extinguisher.

Storage: Store locked up.

Store in a well ventilated place. Keep cool.

Store in well ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container in accordance with local, regional, national, or international regulations.

Chemical Name	Common Name And Synonyms	CAS No. and other Unique identifiers	Concentration %
Isopropanol	Isopropyl alcohol	67-63-0	~85%
Petroleum Distillates	-	64742-47-8	~15%

After Inhalation:

If inhaled: Remove person to fresh air and keep comfortable for breathing. Get medical attention.

After Skin Contact:

If on skin immediately wash with plenty of water. Get medical attention.

After Eye Contact:

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so.

Continue rinsing. Call a physician or poison control center immediately.

After Ingestion:

If swallowed: Rinse mouth. Do NOT induce vomiting.

If swallowed: Immediately flush mouth with plenty of water (If swallowed: Rinse mouth with plenty of water for at least 15 minutes. Do not induce vomiting. Call a physician or poison control center immediately.)

**Personal Precautions,
Protective Equipment, &
Emergency Proc**

Wear chemical goggle, gloves and face shield and protective clothing.

Prevent spilled product from drains, sewers, waterways and soil.

**Methods and Materials for
containment & cleaning up:**

Provide sufficient ventilation.

Remove or shutdown ignition sources such as pilot lights, heating elements, furnaces and boilers.

Stop leak if possible without risk.

If trained in accordance 29 CFR 1910.120, leaks should be stopped. Spills should be contained and cleaned immediately. Persons performing clean up work should wear adequate personal protective equipment and clothing. Spills and releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

Use only non sparking tools.

Name	Std.	TWA-8hrs	STEL - 15 min.
Isopropanol	ACGIH	400 ppm	500 ppm
Petroleum Distillates	ACGIH	100 ppm	-

ACGIH - American Control of Governmental Hygenists
 OSHA - Occupational Safety and Health Administration

Ventilation: Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit (s) (PEL) or the ACGIH threshold Limit Values (TLV)Time Weight Average (TWA).

Respiratory Protection: A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI 788.2 or applicable federal requirements must be followed whenever work place conditions warrant respirator use. NIOSH's Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Other: Safety shower in work area.

Protective Gloves: Butyl or neoprene gloves

Eye Protection: Wear chemical safety goggles with face shield.

Appearance: Yellow Liquid

Odor: alcohol odor

Odor Threshold: N/A

PH: 7-9 in 1% Water

Melting Point/Freezing Point: N/A

Initial Boiling Point and Boiling Range: N/A

Flash Point: N/A

Evaporation Rate: N/A

Flammability (solid, gas): N/A

Upper/Lower flammability or explosive limits: N/A

Vapor Pressure: 33 mm Hg at 68 °F

Vapor Density: >1 (Air=1)

Relative Density: 0.79-0.80

Solubility (ies): Dispersible

Partition Coefficient; n-octanol/water: N/A

Auto-ignition Temperature: N/A

Decomposition Temperature: N/A

Viscosity: N/A

Chemical Stability: Stable under normal conditions

Conditions to Avoid: Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions.

Incompatible Materials: Avoid contact with strong oxidizers and strong acids.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

Oral Administration: Isopropanol-LD50-(Rat)-4700-5800 mg/kg
Oral Administration: Petroleum Distillates,hydrotreated light -LD50(Rat)->5 g/kg
Inhalation: Isopropanol-LC50(Rat)-16,000 ppm
Dermal administration: Isopropanol-LD50(Rabbit)-13,000 mg/kg
Dermal administration: Petroleum Distillates,hydrotreated light-LD50(Rabbit)->3 g/kg
Sensitization: Based on available data, the classification criteria is not met.
Cancer Hazard: Isopropyl Alcohol-IARC Group 3- Not classifiable as to its carcinogenicity to humans
Routes of Exposure Eyes, Skin, Inhalation, Ingestion

Daphnia Magna, Isopropanol-EC50-5102 mg/L 24 h
Persistence and Will biodegrade readily
Degradability:
Bioaccumulation potential: Unlikely
Disperses in water.