6/28/21

BLACK-MAGIC® RT Z40 2260008

Industrial applications



| Nickel Sulfate hexahydrate | - | 10101-97-0 | 1-3% |
|-----------------------------|--------|------------|------|
| Antimony Potassium Tartrate | Tartar | 28300-74-5 | ~5% |
| Sodium Thiocyanate | - | 540-72-7 | <3% |

Remove exposed person to fresh air and support breathing as needed.

Immediately remove contaminated clothing under a safety shower. Flush all affected areas with large amounts of water for 15 minutes. DO NOT attempt to neutralize with chemical agents. Obtain medical advice.

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Do not induce vomiting. Immediately rinse mouth and drink plenty of water. If vomiting occurs, keep head low so that the stomach content doesn't get into the lungs. Never give anything by mouth to an unconscious person. Do not use mouth-to-mouth method if victim ingested the substance.

Symptons may include irriitation to the nose, throat and upper respiratory tract.

Adverse symptons may include the following: Symptons may include redness, pain, blurred vision, eye burns and permanent eye damage.

Adverse symptons may include the following: May cause redness, pain and severe skin burns.

Adverse symptons may include the following: Symptons may include severe burns of the mouth, throat and stomach. Ingestion of large quantities may cause gastrointestinal irritation, vomiting and diarrhea.

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Fire fighters should enter area only if they are protected from all contact with the materail. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

Wear chemical goggle, gloves and face shield and protective clothing.

Prevent spilled product from drains, sewers, waterways and soil.

Absorb the chemical onto sand, vermiculite, or any other non-combustible absorbent, and collect into containers for later disposal.

If trained in accordance 29 CFR 1910.120, leaks should be stopped. Spills should be contained and cleaned immediately. Persons performing clean up work should wear adequate personal protective equipment and clothing. Spills and releases should be reported, if required, to the appropriate local, state and federal regulatory agencies.

Avoid breathing dust, fumes, gas, mist, vapors and sprays.

Wash hands thoroughly after handling.

Do not get in eyes, or on skin, or on clothing.

Keep container tightly closed.

Do not allow material to freeze.

Store in corrosive resistant container.

| Nickel Sulfate | OSHA | 1 mg/m3 | |
|-----------------------------|-----------------|-----------|---|
| Antimony Potassium Tartrate | ACGIH | 0.5 mg/m3 | - |
| Sodium Thiocyanate | Not established | | |

Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit (s) (Patulidal Jsd))77(patild/Jipfif)[TJ36 Tpu73rdase0 T(STep co)-367N6Rc 8.9e forn7(enti87)17()]T Tpu73d.W

Nickel Compounds-SARA 313 listed

WARNING! This product contains a chemical known in the State of California to cause cancer. Nickel compounds.

All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.