

ELECTROLESS CPR 8100A
2707004

Industrial applications



Formaldehyde	Methyl Aldehyde	50-00-0	<9%
Copper Sulfate	-	7758-98-7	<18%
Methanol	Methyl Alcohol	67-56-1	<4%

Remove exposed person to fresh air and support breathing as needed.

Immediately remove contaminated clothing under a safety shower. Flush all affected areas with large amounts of water for 15 minutes. DO NOT attempt to neutralize with chemical agents. Obtain medical advice.

Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Do not induce vomiting. Immediately rinse mouth and drink plenty of water. If vomiting occurs, keep head low so that the stomach content doesn't get into the lungs. Nontoxif 4y5l2hg. at the 3.9tely rsn'l at

Symptoms may include irritation to the nose, throat and upper respiratory tract.

Selenium dusts produce respiratory tract irritation manifested by nasal discharge, loss of smell, epistaxis, and cough. A group of workers exposed to undetermined amounts of selenium oxide developed severe irritation of the eyes, nose, and throat, followed by headaches.

Adverse symptoms may include the following: Symptoms may include redness, pain, blurred vision, eye burns and permanent eye damage.

Adverse symptoms may include the following: May cause redness, pain and severe skin burns.

Adverse symptoms may include the following: Symptoms may include severe burns of the mouth, throat and stomach. Ingestion of large quantities may cause gastrointestinal irritation, vomiting and diarrhea.

Will not burn or support combustion. Use extinguishing media appropriate for surrounding fire, such as water spray, dry chemical, foam or carbon dioxide.

Fire fighters should enter area only if they are protected from all contact with the material. Full protective clothing, including self-contained breathing apparatus, coat, pants, gloves, boots and bands around legs, arms, and waist, should be worn. No skin surfaces should be exposed.

Wear chemical goggles, gloves and face shield and protective clothing.

Prevent spilled product from drains, sewers, waterways and soil.

Absorb the chemical onto sand, vermiculite, or any other non-combustible absorbent, and collect into containers for later disposal.

Avoid breathing dust, fumes, gas, mist, vapors and sprays.

Wash hands thoroughly after handling.

Do not get in eyes, or on skin, or on clothing.

Keep container tightly closed.

Do not allow material to freeze.

Store in corrosive resistant container.

Formaldehyde	ACGIH	0.3 ppm	2 ppm
Methanol	ACGIH	200 ppm	250 ppm (skin)
Cupric Acid	ACGIH	1 mg/m ³ as Cu	-

Use local exhaust to keep personal exposures below the OSHA Permissible Exposure Limit (s) (PEL) or the ACGIH threshold Limit Values (TLV)Time Weight Average (TWA).

Not required if proper ventilation controls are employed.

Acid resistant rubber.

Wear chemical safety goggles.

Irritation or burns to skin, eyes and respiratory system

Formaldehyde-IARC Group 1-Carcinogenic to humans,NTP-known to be human carcinogen,OSHA -specifically regulated carcinogen.

Eyes, Skin, Inhalation, Ingestion

Copper Sulfate-LC50-0.182 mg/L 24 hrs

Not Available

Not known

No data available

Not known

Dispose of in accordance with local, state and federal regulations.

3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,LIQUID,N.O.S.(CUPRIC SULPHATE,
FORMALDEHYDE SOLUTION),

9, MARINE POLLUTANT

III

171

Copper Sulfate-RQ is 10 lbs

Copper Compounds-SARA 313 listed

Methanol-SARA 313 listed

Formaldehyde-SARA 313 listed

No Proposition 65 listed components in this formula

All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements .

The information is based on our knowledge to date but does not constitute an assurance of product properties and does not imply a legal contractual relationship.